

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Magnesium XL FS

As part of the kits: 1 4610 XX XX XXX
(The positions X code different packages.)

UFI: NK20-C0G0-J00F-PCJY

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Reagent for in-vitro diagnostics in human samples
For professional use only.

1.3 Details of the supplier of the safety data sheet

Company name: DiaSys Diagnostic Systems GmbH

Street/POB-No.: Alte Strasse 9

Postal Code, city: 65558 Holzheim

WWW: <http://www.diasys.de>

E-mail: mail@diasys.de

Telephone: +49 (0) 6432-9146-0

Telefax: +49 (0) 6432-9146-32

Department responsible for information:

Corporate headquarters, Telephone: +49 (0) 6432-9146-0, Email: mail@diasys.de

1.4 Emergency telephone number

Infraserv, Telephone: +49 (0) 69-305-6418

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Skin Irrit. 2; H315 Causes skin irritation.

Eye Dam. 1; H318 Causes serious eye damage.


2.2 Label elements

Labelling (CLP)



Signal word: **Danger**

Hazard statements: H315 Causes skin irritation.
H318 Causes serious eye damage.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 14/7/2022
Version: 19.0
Language: en-GB,IE
Date of print: 6/9/2022

Magnesium XL FS

Material number 1 4610

Page: 2 of 9

Precautionary statements:

- P264 Wash hands and face thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

Special labelling

Text for labelling: Contains Ethanolamine.

2.3 Other hazards

No risks worthy of mention.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Aqueous solution

Hazardous ingredients:

Ingredient	Designation	Content	Classification
EC No. 205-483-3 CAS 141-43-5	Ethanolamine	1 - 5 %	Acute Tox. 4; H302. Acute Tox. 4; H312. Acute Tox. 4; H332. Skin Corr. 1B; H314. STOT SE 3; H335. Aquatic Chronic 3; H412.

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General information: First aider: Pay attention to self-protection!
If medical advice is needed, have product container or label at hand.
Take off contaminated clothing and wash it before reuse.
- In case of inhalation: Provide fresh air. Seek medical treatment in case of troubles.
- Following skin contact: After contact with skin, wash immediately with plenty of water. In case of skin irritation, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently seek the immediate attention of an ophthalmologist.
- After swallowing: Rinse mouth immediately and drink plenty of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Product is non-combustible. Extinguishing materials should therefore be selected according to surroundings.

5.2 Special hazards arising from the substance or mixture

Fires in the immediate vicinity may cause the development of dangerous vapours. In case of fire may be liberated: Nitrogen oxides (NO_x), carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained breathing apparatus.

Additional information:

Hazchem-Code: -

Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear appropriate protective equipment. Ensure adequate ventilation, especially in confined areas. Do not breathe vapours. Keep unprotected people away. Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance. Final cleaning.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation. Avoid contact with skin and eyes. Do not breathe vapours. Wear appropriate protective equipment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep containers tightly closed and at a temperature between 2 °C and 8 °C. Keep sterile. Do not freeze.

Unsuitable materials: Copper

Hints on joint storage:

Do not store together with strong acids.

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
141-43-5	Ethanolamine	Europe: IOELV: STEL	7.6 mg/m ³ ; 3 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	2.5 mg/m ³ ; 1 ppm (may be absorbed through the skin)
		Great Britain: WEL-STEL	7.6 mg/m ³ ; 3 ppm (may be absorbed through the skin)
		Great Britain: WEL-TWA	2.5 mg/m ³ ; 1 ppm (may be absorbed through the skin)
		Ireland: 15 minutes	7.6 mg/m ³ ; 3 ppm (may be absorbed through the skin)
		Ireland: 8 hours	2.5 mg/m ³ ; 1 ppm (may be absorbed through the skin)
		Ireland: 8 hours	2.5 mg/m ³ ; 1 ppm (may be absorbed through the skin)

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

Personal protection equipment

Occupational exposure controls

- Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387.
- Hand protection: Protective gloves according to EN 374.
Glove material: Natural latex - Layer thickness: 0.6 mm
Breakthrough time: >480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed goggles according to EN 166.
- Body protection: Wear suitable protective clothing.
- General protection and hygiene measures:
Do not breathe vapours. Avoid contact with skin and eyes. Wash hands before breaks and after work. When using do not eat, drink or smoke. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance: Physical state at 20 °C and 101.3 kPa: liquid
Colour: blue, clear

Magnesium XL FS

Material number 1 4610

Page: 5 of 9

Odour:	odourless
Odour threshold:	No data available
pH:	at 25 °C: 11
Melting point/freezing point:	approx. 0 °C
Initial boiling point and boiling range:	approx. 100 °C
Flash point/flash point range:	not combustible
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapour pressure:	No data available
Vapour density:	No data available
Density:	at 20 °C: 1.002 g/mL
Water solubility:	at 20 °C: completely miscible
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	No data available
Explosive properties:	No data available
Oxidizing characteristics:	No data available

9.2 Other information

Additional information: No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

refer to 10.3

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known.

10.4 Conditions to avoid

Protect against heat /sun rays.

10.5 Incompatible materials

Strong acids, copper

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Skin Irrit. 2; H315 = Causes skin irritation.

Serious eye damage/irritation: Eye Dam. 1; H318 = Causes serious eye damage.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: In case of spills of large quantities: Harmful effects on water organisms by modification of pH-value.

12.2 Persistence and degradability

Further details: The following applies to Ethanolamine in general:
Biodegradability: > 70 %/ 28 d (OECD 301 E). Product is readily biodegradable.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 14/7/2022
Version: 19.0
Language: en-GB,IE
Date of print: 6/9/2022

Magnesium XL FS

Material number 1 4610

Page: 7 of 9

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 05 06* = Laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals.

* = Evidence for disposal must be provided.

Recommendation: Special waste. Dispose of waste according to applicable legislation.

Package

Waste key number: 15 01 02 = Plastic packaging

Recommendation: Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR:
not applicable

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:
Not restricted

14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR:
not applicable

14.4 Packing group

ADR/RID, IMDG, IATA-DGR:
not applicable

14.5 Environmental hazards

Marine pollutant: no

14.6 Special precautions for user

No dangerous good in sense of these transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: -
No data available

National regulations - EC member states

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

H302 = Harmful if swallowed.
H312 = Harmful in contact with skin.
H314 = Causes severe skin burns and eye damage.
H315 = Causes skin irritation.
H318 = Causes serious eye damage.
H332 = Harmful if inhaled.
H335 = May cause respiratory irritation.
H412 = Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
AS/NZS: Australian Standards/New Zealand Standards
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EN: European Standard
EQ: Excepted quantities
EU: European Union
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 14/7/2022
Version: 19.0
Language: en-GB,IE
Date of print: 6/9/2022

Magnesium XL FS

Material number 1 4610

Page: 9 of 9

Reason of change: Changes in section 1: Product Identification

Date of first version: 31/7/2007

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.